




100/1000 Base T Gigabit Single PoE Plus

AGSC-2417PS

- PoE Plus with 720mA Current Capability
- Compliant to IEEE802.3at / ANSI X3.263
- LL: 0.5μH Max @ 100KHz, 200mV
- Cw/w: 25PF TYP @ 100KHz, 200mV
- DCR: 0.9Ω Max
- Operating Temp: 0°C to +70°C



Electrical Specifications @ 25°C


OCL(μH Min) @ 100kHz, 200mV With 8mA DC Bias	Turns Ratio chip: cable (±5%)	Insertion Loss (dB Max)	Return Loss (dB Min)			
		0.3-100MHz	0.3-30MHz	40MHz	50MHz	60-80MHz
350	1CT:1CT	-1.1	-18	-14.4	-13.1	-12

Electrical Specifications @ 25°C

Common Mode Rejection (dB Min)			Cross Talk (dB Min)		Isolation Hi-Pot (Vrms)
30MHz	60MHz	80-100MHz	0.3-60MHz	60-100MHz	
-40	-35	-30	-35	-32	1500

All specifications subject to change without notice.

MECHANICAL

Dimensions: $\frac{\text{inch}}{\text{(mm)}}$ 

SCHEMATICS

Unless otherwise specified, all tolerances are ±.010(0.25)

