

4XEM's 3-in-1 USB-C Hub with 4K HDMI and USB 3.0

4XEM Part- 4XUSBCHUB02



4XEM's 3-in-1 USB-C Docking station creates a high functioning centre for any tech space. Fitted with an HDMI port, USB 3.0 port with USB-C connectors this Docking station is a premier central hub for multiple devices. The station offers the ability to charge with the USB 3.0 Power delivery while simultaneously connect HDMI monitors with 4K video resolution.

Problem it solves: Complete multiple functions with 4XEM's 3-in-1 USB-C Docking Station. The Docking Station enables charging and transferring with USB-C and USB power delivery, it also allows you to connect 4K HDMI monitors with only one device.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Brandon Hegarty 4XEM Sales Manager
1-866-999-4936 Ext.113 bhegarty@4xem.com



Features

- USB-C 3.1 Gen 1 (5 Gbps) Host connector –Attached
- 1x HDMI 2.0 port
- 1x USB 3.0 Type-A port (5 Gbps)
- 1x USB Type-C port (No Data – USB PD Charge only)
- Supports 4K UHD video resolution (3840x2160 @ 30Hz)
- Supports PD Pass-through – Max 100W
- Windows 10 and Mac OS11 compatible
- DP Alt mode from host required got full video functionality
- USB-PD support from host required for full PD functionality

Application

- **Enhanced Connectivity:** Expand your device's capabilities with the docking station's USB 3.0 Type-A port, enabling high-speed data transfer and seamless connection to various peripherals.
- **Stunning 4K Visuals:** Enjoy immersive visual experiences with support for 4K resolutions, delivering crisp and detailed images on your connected display.
- **Versatile Audio Output:** Immerse yourself in up to 8-channel surround sound through the HDMI connection, enhancing your multimedia experience and ensuring superior audio quality.
- **Convenient Power Delivery:** Utilize the Power Delivery (PD 3.0) feature to efficiently charge your devices while connected, providing a reliable power source and eliminating the need for additional chargers.



4XEM Products Are Available At Your Favorite Online Retailers



Warranty Information	Warranty	3 Years
Features	4K Support Displays Supported USB Ports Fast-Charge Port(s) Network Media Card Reader Audio Power Delivery	Yes 1 1 No No No Yes* Yes
Hardware	Chipset ID Industry Standards	ALGOLTEK AG9311 Shenzhen Legendary Technologies - LDR6023S HDMI 2.0** HDCP 1.4 HDCP 2.3 Power Delivery (PD 3.0)
Connector(s)/Performance	Host Bus Type Host Connector Host Connector Type Connector Type(s)/Rate(s) Maximum Digital Resolutions Maximum Analog Resolutions Audio Specification	USB 3.1 Gen 1 (5Gbps) USB Type-C Fixed Attached Cable 1x HDMI 2.0 (Limited Bandwidth - 10.8 Gbps) 1x USB 3.0 Type-A (5 Gbps) 1x USB Type-C (No Data - USB-PD Input Only) 4K UHD (3840 x 2160 @ 30Hz, 8bpc) N/A Up to 8-ch Surround (via HDMI)
Software	OS Compatibility	Windows® 10 Mac OS® 11
Power	Power Source Power Consumption Power Delivery	Bus Powered 15W PD Pass-Through - Max 100W
Physical Characteristics	Color Shell Material LED Indicators Attached Cable Length Product Height Product Width Product Length (Body) Product Length (Overall) Weight of Product	Silver, White Aluminum, Plastic None 2.95 in [75.0 mm] 0.60 in [15.3 mm] 2.93 in [74.3 mm] 1.29 in [38.2 mm] 6.07 in [154.2 mm] 1.55 oz [44 g]
Environmental	Operating Temperature Storage Temperature	14°F to 113°F [-10°C to 45°C] @ 5%-95% RH (Non-Condensing) -4°F to 149°F [-10°C to 65°C] @ 5%-95% RH (Non-Condensing)
Packaging Information	Package Type Package Height Package Width Package Length Shipping (Package) Weight	Poly-Bag 9.84 in [250.0 mm] 5.02 in [127.4 mm] 0.61 in [15.5 mm] 1.83 oz [52 g]
What's in the Box	Included in Package	1x USB-C Hub
Notes / Special Requirements	Requirements Notes	DP-Alt mode and USB-PD support from host required to ensure full functionality. "Some hardware may have specific power requirements. For example, if your laptop expects 60W of power and an adapter consumes some of the 60W, your hardware/operating system may display a "slow charging" message. This adapter uses 2 DP lanes @ HBR2 for alt mode video output resulting in a lower bandwidth implementation of the HDMI 2.0 specification. Audio output only available via HDMI."

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

