

4XEM's 3-in-1 USB-C Docking Station with 4K HDMI and USB 3.0

4XEM Part- 4XUSBCHUB01



4XEM's 3-in-1 USB-C Docking station creates a high functioning centre for any tech space. Fitted with an HDMI port, USB 3.0 port with USB-C connectors this Docking station is a premier central hub for multiple devices. The station offers the ability to charge with the USB 3.0 Power delivery while simultaneously connect HDMI monitors with 4K video resolution.

**Problem it solves:** Complete multiple functions with 4XEM's 3-in-1 USB-C Docking Station. The Docking Station enables charging and transferring with USB-C and USB power delivery, it also allows you to connect 4K HDMI monitors with only one device.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Brandon Hegarty 4XEM Sales Manager**  
**1-866-999-4936 Ext.113    bhegarty@4xem.com**



## Features

- USB-C 3.1 Gen 1 (5 Gbps) Host connector –Attached
- 1x HDMI 2.0 port
- 1x USB 3.0 Type-A port (5 Gbps)
- 1x USB Type-C port (No Data – USB PD Charge only)
- Supports 4K UHD video resolution (3840x2160 @ 30Hz)
- Supports PD Pass-through – Max 100W
- Windows 10 and Mac OS11 compatible
- DP Alt mode from host required got full video functionality
- USB-PD support from host required for full PD functionality

## Application


- **Enhanced Connectivity:** Expand your device's capabilities with the docking station's USB 3.0 Type-A port, enabling high-speed data transfer and seamless connection to various peripherals.
- **Stunning 4K Visuals:** Enjoy immersive visual experiences with support for 4K resolutions, delivering crisp and detailed images on your connected display.
- **Versatile Audio Output:** Immerse yourself in up to 8-channel surround sound through the HDMI connection, enhancing your multimedia experience and ensuring superior audio quality.
- **Convenient Power Delivery:** Utilize the Power Delivery (PD 3.0) feature to efficiently charge your devices while connected, providing a reliable power source and eliminating the need for additional chargers.



USB-C Male



USB-C Female



HDMI Port



USB-A (3.0) Port

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Brandon Hegarty 4XEM Sales Manager  
1-866-999-4936 Ext.113    bhegarty@4xem.com





## DATA SHEET

|                              |                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Warranty Information         | Warranty                                                                                                                                                                        | 3 Years                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Features                     | 4K Support<br>Displays Supported<br>USB Ports<br>Fast-Charge Port(s)<br>Network<br>Media Card Reader<br>Audio<br>Power Delivery                                                 | Yes<br>1<br>1<br>No<br>No<br>No<br>Yes*<br>Yes                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Hardware                     | Chipset ID<br><br>Industry Standards                                                                                                                                            | Parade Technologies - PS176<br>Shenzhen Legendary Technologies - LDR6023S<br>HDMI 2.0**<br>HDCP 1.4<br>HDCP 2.3<br>Power Delivery (PD 3.0)                                                                                                                                                                                                                                                                                                                                                |
| Connector(s)/Performance     | Host Bus Type<br>Host Connector<br>Host Connector Type<br>Connector Type(s)/Rate(s)<br><br>Maximum Digital Resolutions<br>Maximum Analog Resolutions<br>Audio Specification     | USB 3.1 Gen 1 (5Gbps)<br>USB Type-C<br>Fixed Attached Cable<br>1x HDMI 2.0 (Limited Bandwidth - 10.8 Gbps)<br>1x USB 3.0 Type-A (5 Gbps)<br>1x USB Type-C (No Data - USB-PD Input Only)<br>4K UHD (3840 x 2160 @ 30Hz, 8bpc)<br>N/A<br>Up to 8-ch Surround (via HDMI)                                                                                                                                                                                                                     |
| Software                     | OS Compatibility                                                                                                                                                                | Windows® 10<br>Mac OS® 11                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Power                        | Power Source<br>Power Consumption<br>Power Delivery                                                                                                                             | Bus Powered<br>15W<br>PD Pass-Through - Max 100W                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Physical Characteristics     | Color<br>Shell Material<br>LED Indicators<br>Attached Cable Length<br>Product Height<br>Product Width<br>Product Length (Body)<br>Product Length (Overall)<br>Weight of Product | Silver, White<br>Aluminum, Plastic<br>None<br>2.95 in [75.0 mm]<br>0.60 in [15.3 mm]<br>2.93 in [74.3 mm]<br>1.29 in [38.2 mm]<br>6.07 in [154.2 mm]<br>1.55 oz [44 g]                                                                                                                                                                                                                                                                                                                    |
| Environmental                | Operating Temperature<br>Storage Temperature                                                                                                                                    | 14°F to 113°F [-10°C to 45°C] @ 5%-95% RH (Non-Condensing)<br>-4°F to 149°F [-10°C to 65°C] @ 5%-95% RH (Non-Condensing)                                                                                                                                                                                                                                                                                                                                                                  |
| Packaging Information        | Package Type<br>Package Height<br>Package Width<br>Package Length<br>Shipping (Package) Weight                                                                                  | Poly-Bag<br>9.84 in [250.0 mm]<br>5.02 in [127.4 mm]<br>0.61 in [15.5 mm]<br>1.83 oz [52 g]                                                                                                                                                                                                                                                                                                                                                                                               |
| What's in the Box            | Included in Package                                                                                                                                                             | 1x USB-C Hub                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Notes / Special Requirements | Requirements<br>Notes                                                                                                                                                           | DP-Alt mode and USB-PD support from host required to ensure full functionality.<br>"Some hardware may have specific power requirements. For example, if your laptop expects 60W of power and an adapter consumes some of the 60W, your hardware/operating system may display a "slow charging" message. This adapter uses 2 DP lanes @ HBR2 for alt mode video output resulting in a lower bandwidth implementation of the HDMI 2.0 specification. Audio output only available via HDMI." |

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.

