

4XEM 4 Port HDMI Splitter Supports 3D 4K/2K

4XEM Part - 4XHDMI44K2K



Split the UHD 3D 4K/2K signal from one HDMI device into four using 4XEM's 1x4 3D 4K/2K HDMI splitter (4XHDMI44K2K). Simply connect your 3D or 4K/2K Displays to the splitter's outputs.

Problem it solves: Display your video on multiple HDMI compatible televisions or monitors. Ideal for retail displays, trade shows, sports bar, etc.

4XEM gear is respected industry wide for its high performance, premium quality and our after sales support.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Brandon Hegarty 4XEM Sales Manager
1-866-999-4936 Ext.113 bhegarty@4xem.com



Features:

- Split CATV and other signals with this satellite splitter so that it can be used for more than one device
- Works on 340 MHz maximum frequency for efficient performance
- HDMI interface allows you to connect to a variety of HD devices for the ultimate true high-definition video
- Features HDMI port for delivering and transferring high-quality picture and sound simultaneously at a high-speed.

Applications:

- Multi-Display Broadcasting: Distribute one HDMI source to up to four displays simultaneously for wider viewing.
- 4K Ultra HD Support: Delivers sharp, high-resolution video at up to 4K/2K, ensuring excellent image quality across all screens.
- 3D Content Ready: Fully compatible with 3D video formats, making it ideal for immersive home theater setups.
- Retail & Digital Signage: Display promotional content across multiple 4K screens in stores, showrooms, or event spaces.
- Corporate Presentations: Share a single video feed to multiple displays in conference rooms or training environments.



4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

**Contact Brandon Hegarty 4XEM Sales Manager
1-866-999-4936 Ext.113 bhegarty@4xem.com**



Specifications:

Warranty Information	Warranty:	Lifetime
Connector(s)	Ports:	1x HDMI Female (in) 4x HDMI Female (out) Direct
	Power:	Attached
Power	Power Delivery:	N/A
	Input Voltage:	AC (50HZ, 60HZ) 100V-240V
	Output Voltage:	0.5~1.5Volts p-p(TTL)
Environmental	Operating Temperature:	0 to 40°C (32 to 104°F)
	Storage Temperature:	-20 to 80°C (-4 to 176°F)
	Humidity:	5% to 90% (non-condensing)
What's in the Box	Included in Package:	1 - 4 Port HDMI Splitter

* Product appearance and specifications are subject to change without notice.

* All Specs, Weights and Measurements are approximate.

* Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

**Contact Brandon Hegarty 4XEM Sales Manager
1-866-999-4936 Ext.113 bhegarty@4xem.com**

