

AEONS 19" 1U Rack Mount PDU, Surge Protector, 10 Outlets 15A Switch, 10ft Power Cord PDHS1015N10



Highlights

- Universal 19-inch rack compatible for horizontal or vertical installation
- Ultra-slim 1U form factor saves valuable rack space
- 10 right-angle outlets designed to fit bulky power adapters
- Integrated surge protector, overload protection with illuminated, protected power switch
- Durable aluminum housing for lightweight strength and long service life
- UL-registered with 14AWG heavy-duty power cable for safe operation
- Flexible mounting options for rack, wall, or surface installations

Description

The AEONS 1U SlimRack™ PDU delivers reliable, space-efficient power distribution for modern data centers, network closets, and edge deployments. Designed with an ultra-slim metal housing and right-angle outlets, it maximizes outlet usability while minimizing rack footprint. Built for safety and durability, it features overload protection, a guarded illuminated power switch, and UL-certified construction. Whether deployed horizontally or vertically, this PDU offers a clean, professional power solution for mission-critical environments.

Features

Reliable Power & Equipment Protection

- 10 right-angle outlets accommodate large transformers without blocking
- Built-in SPD surge protector and overload protection
- Secure lighted On/Off switch with protective cover prevents accidental shutdown
- 10-ft heavy-duty 14AWG power cord for installation flexibility

Durable, Professional-Grade Construction

- Ultra-slim aluminum alloy housing—lightweight yet rugged
- Fire-resistant metal enclosure designed for continuous operation
- Powder-coated finish for corrosion resistance and long-term durability
- UL registered for safety and compliance

Space-Optimized & Flexible Installation

- Ready to mount with included mounting hardware to a standard EIA 19-inch racks
- Supports horizontal or vertical mounting
- Detachable mounting flanges enable rack, wall, counter, or surface installation

Specifications

Overview	
Model	PDHS1015N10
Type	Basic
Style	19" 1U Rack Mount
Physical	
Rack Height / Form Factors	1U rackmount, 0U vertical rackmount, undercounter , wallmount
Rack Depth (in. / mm)	2.75 / 70
Unit Dimensions (H x W x D / in.)	1.75 x 19 x 2.4
Unit weight (lbs)	2.5
Shipping Dimensions (H x W x D /	20 x 6 x 3
Shipping weight (lbs)	3
Material	Aluminum
Color	Black
Electrical	
Input	15A 120V Single-Phase
Input Connection Type	NEMA 5-15P
Input Cord Length (ft / m)	10 / 3 14AWG power cable
Output Capacity	1.8KW 120V 15A total capacity
Output Receptacles	(10) NEMA 5-15R
Other	Power Switch, 15A Overload Protection, SPD Surge Protector
Standards & Compliance	
Compliance	RoHS, EIA/ECA-310-E
Warranty	
Warranty Period	5-year limited warranty